

Skalcem House Protection

Safety data sheet

Last printed on 29.05.2006 11:12

1. Identification of substance/preparation and manufacturer

Product name: SKALCEM HOUSE PROTECTION

Product No.: 1236040

Application: Mix with water and apply as putty

Packaging: 4 kg bucket/10 kg bucket/20 kg bag

Manufacturer: SKALFLEX A/S

Industrivej 20b

DK-8800 Viborg

Tel. +45 8661 2299 Fax +45 8661 2199

email: mail@skalflex.dk

2. Composition/information on ingredients

Ingredients	CAS No.	weight%	classification
Cement	65997-15-1	20-40	Xi;R37/38-41
Fillers, pigments			

3. Hazards identification

The product contains cement which can cause irritation to eyes and skin (especially upon contact with water) and airways.

4. First-aid measures

Inhalation:

Seek fresh air. If discomfort persists, get medical assistance.

Skin contact:

Remove contaminated clothes. Wash off skin with plenty of water and soap.

Then apply a rich cream to the skin. Get medical assistance if irritation does not clear.

Eye contact:

Open eyelids widely and rinse eye with plenty of water for at least 15 minutes. Get medical assistance if irritation does not clear immediately.

Ingestion:

Do not induce vomiting. Let victim drink plenty of water or milk and get medical assistance immediately.

5. Fire fighting measures

The product is not flammable.

6. Accidental release measures

Hand-over large spills to municipal receiving facility. Also see item 13. Capture spills with vacuum cleaner. Avoid inhalation of dust.

7. Handling and storage

Avoid direct contact with product, especially after product has been mixed. Use protective gloves and guard, if necessary. See item 8.

Use approved respiratory protection for dusty work. See item 8.

Store product in closed original container.

Fire rating: - (see item 5)

8. Exposure controls/personal protection

The following contents are subject to disclosure regulations and have exposure limits:

Mineral dust (inert)	10mg/m ³
Silicon dioxide, crystalline, total	0.3mg/m ³
Silicon dioxide, respirable	0.1mg/m ³

If necessary, the following personal protective equipment is recommended:

Respiratory protection:	Rubber half mask/P2 filters.
Gloves:	Rubber/PVC
Eye protection:	Goggles/guard, if necessary

9. Physical and chemical properties

Appearance:	Powder	Solubility in water	*
Odour	*	Distribution coefficient	*
pH	10-11	Flash point	*
Boiling temperature	*	Auto ignition temperature	*
Melting temperature	*	Explosive limit	*

The product is not considered dangerous goods for transportation.

15. Regulatory information

Hazard label on container:

Irritant (Xi)

Irritating to respiratory system and skin (R37/38)

Risk of serious damage to eyes (R41)

Do not breathe dust (S22)

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice (S26)

Wear eye/face protection (S39)

Code No. 00-4 (1993)

Chromate contents: less than 2mg/kg dry product

Application limitation: Not to be used by persons under 18 years of age (apprentices excepted)

Requirements for special training: None

In addition, the product is subject to the following special executive orders:

Order on work with code-numbered products, no. 302 of 13 May 1993.

Order on measures for the prevention of cancer risk when working with substances and materials, no. 140 of February 1997

Order on water-soluble chromates in cement, no. 661 of 1983.

16. Other information

None