

Skalflex Facade Silicate Paint

Material Safety Data Sheet
Printed 07-07-03 13:53

Page 1 of 3

1. Identification of the material & supplier

Product name: Skalflex Facade Silicate Paint
Intended use: Paint
Package: 5 and 10 l. buckets
Producer: SKALFLEX A/S
Industrivej 20b
DK-8800 Viborg
Tlf. +45 8661 2299 Fax. +45 8661 2199

2. Composition/Information on Ingredients:

Waterborne paint. Contains alkali silicates

3. Hazards Identification:

Skin- and eye contact may course irritation.

4. First-Aid-Measures:

Inhalation: Move into fresh air and keep at rest

Skin contact: Remove contaminated clothes and rinse skin thoroughly with water.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Continue flushing during transport to hospital. Bring along these instructions.

Ingestion: Immediately rinse mouth and drink plenty of liquid. Keep person under observation. If uncomfortable: Seek hospital and bring these instructions.

5. Fire-fighting Measures

None specific. Use fire-extinguishing media appropriate for surrounding materials.

6. Accidental Release Measures

Avoid contact with the product. Personal protection: see section 8.
Avoid discharge into drains, water courses or onto the ground.

Skalflex Facade Silicate Paint

Material Safety Data Sheet
Printed 07-07-03 13:53

Page 2 of 3

Dam and absorb spillage with sand, sawdust or other inert absorbent. For waste disposal see section 13.

7. Handling and Storage

Avoid inhalation of vapours and contact with skin and eyes. Observe good industrial hygiene practices.

Store in closed original container in a dry place.

8. Exposure Controls and Personal Protection

Personal protection: Use overall
Gloves: Rubber/PVC
Eye protection: Glasses

9. Fysisk-kemiske egenskaber:

Appearance:	liquid	Solubility-water	Completely
Odour	*	n-octanol/water	*
pH	*	Flash-point	*
Boiling point	100°	Autoignition	*
Melting point	*	Explosive properties	*
Vapour pressure	*	Viscosity	*
Density	*	Other data	*

*: Means no data or not relevant

10. Stability an Reactivity

Stability: Stable

11. Toxicological Information

Inhalation:

None by ordinary use.

Skincontact:

Slightly irritating. Prolonged contact may cause redness, itching, eczema and irritation.

Eye contact:

May be irritating and may cause redness and pain.

Ingestion:

May be irritating. May cause nausea, stomach pain and vomiting.

Skalflex Facade Silicate Paint

Material Safety Data Sheet
Printed 07-07-03 13:53

Page 3 of 3

12. Ecological Information

There is no data available for the product itself.

Do not allow to contaminate drains, sewers or water courses.

13. Disposal Considerations

Dispose of in accordance with Local Authority requirements.
Contact specialist disposal companies.

Transportation as waste: see also point 14

14. Transport Information

The product is not considered dangerous goods.

15. Regulation Information

Label for supply

Based on information from the manufacturer regarding the chemical composition of the product, an assessment by the Danish Toxicology Centre on 6 December 1995 has shown that according to EEC Directives 67/548/EEC, the product is not liable to classification and labelling.

Regulations: 1) EEC Directives 67/548/EEC on dangerous substances and 88/379/EEC on dangerous preparations, implemented in Great Britain by the Chemicals (Hazard information Packaging for supply) Regulations 1994. (SI 1994/3247)

16. Other Information

The user must be instructed in the proper work procedure and be familiar with the contents of these instruction
